



## JenLas<sup>®</sup> D2.mini 2/3 W

### Diode-Pumped Thin-Disk Laser



#### Features:

- Minimal dimensions
- Low heat dissipation
- OEM design
- Accessories available

#### Advantages:

- Ideal for small devices
- Low cooling requirements
- Designed for integration
- Complexity reduction

#### Applications:

- Ophthalmology
- Show & Entertainment
- Spectroscopy
- Science
- Pumping of Ti:Sa

# JenLas® D2.mini 2/3 W

## Diode-Pumped Thin-Disk Laser

### Specifications


| Parameters          |   |
|---------------------|---|
| Laser               | frequency-doubled thin-disk laser, diode-pumped |
| Laser class         | 4 (according to EN 60825-1)                     |
| Wavelength          | 532 nm ± 1 nm                                   |
| Ambient temperature | + 5 °C ... + 40 °C                              |

| cw operation                                       |  |
|--|--|
| Output power                                       | 2.0 W or 3.0 W   |
| Power stability (rms)                              | < 3 % (depending on master device)                           |
| Beam quality M <sup>2</sup>                        | < 5 (typical ~ 4) (sufficient for coupling into 50 µm fiber) |
| Beam diameter                                      | ~ 1.5 mm   |
| Divergency   | < 2 mrad (half angle)  |
| Pulse duration, switchable via diode laser current | ~ 1 ms to cw (amplitude modulation up to 50 kHz possible)    |

| Electrical specifications |  |
|---------------------------|--|
| Electrical input data     | 2 V, typical 20 A (at pump diode for 3 W output power) |
| Input power               | < 50 VA  |

| Mechanical specifications |                          |
|---------------------------|--------------------------|
| Dimensions (W x H x L)    | 62 mm x 24 mm x 105.7 mm |
| Weight                    | ~ 0.5 kg                 |

For the operation of the laser, a suitable power supply must be used that complies with the regulations relevant to the respective application. Please contact us for further technical details.



It is our policy to constantly improve the design and specifications. Accordingly, the details represented herein cannot be regarded as final and binding.



JENOPTIK | Lasers & Material Processing

JENOPTIK Laser GmbH

Goeschwitzer Strasse 29 | 07745 Jena | Germany

Phone: +49 3641 65-3053 | Fax: +49 3641 65-4011

E-mail: sales-laser.lm@jenoptik.com | www.jenoptik.com/solidstatelasers

